

Summary of testing:

- 4.3.1 Time interval between intrusion signals or messages
- 6.1 General test conditions
- 6.2 Basic detection test
- 6.3.3.1 Verify detection across the boundary
- 6.3.3.2 Verify detection within the boundary
- 6.3.4 Verify the high velocity detection performance

| EN 50131-2-4 | | | |
|--------------|--------------------------------|-----------------|---------|
| Clause | Requirement – Test | Result - Remark | Verdict |
| 4 | Functional Requirements | | |

EN 50131-2-4

EN 50131-2-4

| Clause | Requirement – Test | Result - Remark | Verdict |
|--------|--------------------|-----------------|---------|
|--------|--------------------|-----------------|---------|

| EN 50131-2-4 | | | |
|--------------|-----------------------------|-----------------|---------|
| Clause | Requirement – Test | Result - Remark | Verdict |
| 6.2 | Basic detection test | | |

EN 50131-2-4

| Clause | Requirement – Test | Result - Remark | Verdict |
|--------|--------------------|-----------------|---------|
|--------|--------------------|-----------------|---------|

EN 50131-2-4


| EN 50131-2-4 | | | |
|--------------|--------------------|-----------------|---------|
| Clause | Requirement – Test | Result - Remark | Verdict |

EN 50131-2-4

EN 50131-2-4

| | | |
|--|--|--|
| | | |
| | | |

EN 50131-2-4



EN 50131-2-4

| Clause | Requirement – Test | Result - Remark | Verdict |
|--------|--------------------|-----------------|---------|
|--------|--------------------|-----------------|---------|

EN 50131-2-4

Result - Remark

Verdict

ATIONAL and ENDURANCE) Pictures



X axis setup



Y axis setup

Z axis setup